

## REBOUND® CLEANER/ENHANCER

Concentrated one step cleaner/enhancer. May be applied by autoscrubber or damp-mop. Cleans and enhances coating for brilliant wet-look shine when burnished with UHS burnishers.

### FEATURES

- Exceptionally slip resistant
- Cleaner and gloss enhancer in one
- Concentrated for economical use
- Pleasant lemon-lime fragrance
- Classified by UL as to slip resistance only



### RECOMMENDED SURFACES

All resilient tile floors and most types of terrazzo, marble, concrete, and quarry tile and treated wood floors

### PRODUCT DATA

Description:	Waterbased cleaner/enhancer
Appearance:	Clear green
Fragrance:	Lemon-lime
Non-Volatile Solids:	11.0 ± 0.5%, ASTM D2834-95 (2001)
Buffability:	Excellent
Viscosity (Brookfield):	<10 centipoise @ 68°F (20°C)
Slip Resistance:	Meets ASTM D2047-99 requirements. Classified by UL as to slip resistance only.
Drying time:	Approximately 15 minutes
Shelf Life:	1 year, ASTM D1791-93 (1998)
Density:	8.5 lb per gal @ 68°F 1.02 kg per liter @ 20°C
Freeze/Thaw:	Passes 3 cycles, ASTM D3209-93 (1998)

### PRECAUTIONS

Keep out of the reach of children. Keep container sealed when not in use. Avoid freezing. If frozen, allow to return to room temperature slowly and then mix thoroughly before using.

### ORDERING INFORMATION

Product #211FS:	2 x 2.50 gallon per case (2 x 9.5 liters)
Product #211MP:	4 x 1.06 gallon per case (4 x 4 liters)

### DIRECTIONS FOR USE: AUTOSCRUBBER APPLICATION

1. Sweep floor with a mop treated with EnviroStar Green® Dust Mop Treatment or an untreated dust mop to remove loose dirt.
2. Mix Rebound Cleaner/Enhancer in an autoscrubber per the following dilution ratio:  
1:32 4 US oz per gallon water (160 ml per 5 liters water)
3. Using a red cleaning pad, scrub and pick up the solution in one pass.
4. Allow floor to dry thoroughly.
5. Burnish with recommended Amano Pioneer Eclipse burnisher and pad.

### DIRECTIONS FOR USE: MOP ON APPLICATION

1. Sweep floor with a mop treated with EnviroStar Green Dust Mop Treatment or an untreated dust mop to remove loose dirt.
2. Mix Rebound Cleaner/Enhancer in mop bucket per the following dilution ratio:  
1:64 2 US oz per gallon water (80 ml per 5 liters water)
3. Damp mop the floor using the solution.
4. Allow floor to dry thoroughly.
5. Burnish with recommended Amano Pioneer Eclipse burnisher and pad.


# REBOUND CLEANER/ENHANCER

**LAST REVISION DATE:** 11/26/07  
**MANUFACTURER:** Amano Pioneer Eclipse® Corp.  
 Sparta, NC 28675 Phone: 1-336-372-8080  
**FOR CHEMICAL EMERGENCY:** Spill, Leak, Fire, Exposure or Accident **CALL CHEMTREC - Day or Night 1-800-424-9300** Toll Free in the Continental US **483-7616** in DISTRICT OF COLUMBIA. For calls originating outside the US: Call Collect **1-202-483-7616** Washington, DC.

**SECTION I: GENERAL INFORMATION**

**PRODUCT NAME:** Rebound® Cleaner/Enhancer  
**PRODUCT #:** 211  
**PRODUCT TYPE:** Waterbased cleaner/enhancer  
**PRECAUTIONS:** Possible skin and eye irritant. Keep container sealed when not in use. Keep out of reach of children.  
**HEALTH:** 1  
**FLAMMABILITY:** 0  
**REACTIVITY:** 0  
**NFPA HAZARD RATINGS**

4-EXTREME 3-HIGH 2-MODERATE  
 1-SLIGHT 0-INSIGNIFICANT



**SECTION II: HAZARDOUS INGREDIENTS**

**INGREDIENT:** Nonionic Surfactant  
**CAS#:** 68439-46-3  
**%:** 5-8  
**OSHA PEL:** N/A  
**ACGIH TLV:** N/A  
**LD<sub>50</sub> SPECIES & ROUTE:** 0.0014 g/kg rat, oral

N/E = Not Established, N/L = Not Listed  
 N/A = Not Applicable

**SECTION III: PHYSICAL/CHEMICAL DATA**

**APPEARANCE:** Clear green  
**PHYSICAL STATE:** Liquid  
**pH:** 9.0 ± 0.5  
**BOILING POINT:** 100°C / 212°F  
**EVAPORATION RATE:** Less than water  
**FREEZING POINT:** 0°C / 32°F  
**VAPOR DENSITY:** Greater than air  
**VOLATILE BY WEIGHT:** 89.0 ± 0.5%  
**VAPOR PRESSURE:** Less than water  
**DENSITY:** 8.5 lb per gal @ 68°F  
 1.02 kg per liter @ 20°C  
**SOLUBILITY IN WATER:** Miscible

**SECTION IV: FIRE AND EXPLOSION DATA**

**FLASH POINT:** Non-combustible  
**EXPLOSIVE LIMITS:**  
 LOWER: N/A UPPER: N/A  
**EXTINGUISHING MEDIA:** N/A  
**SPECIAL FIRE FIGHTING PROCEDURES:** None  
**HAZARDOUS COMBUSTIBLE PRODUCTS:** None  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:**  
 Materials can splatter above 100°C / 212°F.

**SECTION V: REACTIVITY DATA**

**STABILITY:** Stable  
**HAZARDOUS POLYMERIZATION:** Will not occur  
**INCOMPATIBILITY (MATERIALS TO AVOID):**  
 Strong acids and bases.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** N/A  
**REACTIVITY CONDITIONS:** None

**SECTION VI: HEALTH HAZARD DATA**

**EYES:** Slightly irritating to eyes. For eye contact, flush with a large amount of water for at least 15 minutes. See a physician if irritation persists.  
**SKIN:** Slightly irritating to skin upon repeated or prolonged contact. For skin contact, wash affected areas with soap and water.  
**INHALATION:** Vapor or mist may cause irritation of the eyes, nose, throat and lungs. For overexposure, move subject to fresh air.  
**INGESTION:** May cause irritation to mouth, esophagus and stomach. If ingested, drink several glasses of water and do not induce vomiting. Seek medical attention.  
**CHRONIC EFFECTS AND MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:** Prolonged or repeated contact can cause drying, defatting and dermatitis to skin.  
**CARCINOGEN:** Non-carcinogenic  
**REPRODUCTIVE EFFECTS:** N/E  
**TERATOGENICITY:** N/E  
**MUTAGENICITY:** N/E  
**THRESHOLD LIMIT VALUE:** See Section II.

**SECTION VII: SPILL, LEAK & DISPOSAL PROCEDURES**

**SMALL SPILLS:** Absorb spill with inert material (e.g. sand, earth) and dispose of as waste material in accordance with local, state and federal regulations.  
**LARGE SPILLS:** Keep spectators away. Floors may be slippery; use care to avoid falling. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for disposal. Keep spills and cleaning runoff out of sewers and open bodies of water.  
**WASTE DISPOSAL:** Dispose of as waste material in accordance with local, state, and federal regulations.

**SECTION VIII: SPECIAL PROTECTION**

**PERSONAL PROTECTIVE EQUIPMENT (PPE)**  
**EYES:** None required under normal conditions of use. Safety glasses recommended.  
**SKIN:** If prolonged or repeated contact is possible, chemical-resistant clothing (e.g., rubber gloves) is recommended.  
**RESPIRATORY:** No respiratory protection is required if ventilation is adequate.  
**ENGINEERING CONTROLS:** Good general room ventilation is expected to be adequate. Local exhaust ventilation (e.g., fans) may be necessary when general ventilation does not keep airborne concentrations below any exposure limits.

**SECTION IX: SPECIAL PRECAUTIONS**

**HANDLING AND STORAGE:**  
 Storage temperature (MAX. 60°C / 140°F) (MIN. 1°C / 34°F)  
**OTHER PRECAUTIONS:** Keep from freezing; product may coagulate.

**SECTION X: ADDITIONAL INFORMATION**

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which may be the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer based on its own studies and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) or the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

This MSDS has been provided to you in accordance with the OSHA HAZARD COMMUNICATION STANDARD (29CFR1910.1200).

\*\*\*IMPORTANT SAFETY INFORMATION  
 DO NOT DISCARD\*\*\*  
 \*\*PLEASE ROUTE TO COMPANY SAFETY OFFICER\*\*

