

barracuda[®]

Low Profile Propane Stripping Machine

FEATURES:

- Available in 30", 34" & 38" models
- 30"/431 cc OHV V-VALVE Kawasaki engine
34" & 38"/585 cc OHV V-VALVE Kawasaki engine
- 2 year engine warranty
(4 year option using Kawasaki approved oil)
- Partially enclosed body style enhances public-friendly appearance
- Low profile deck (under 4"/10 cm) for edge to edge operation
- RokBak™ deck for easy brush/pad installation from standing position
- Counter-rotating brushes reduce strip splash
- Bail throttle with electronic clutch ensures smooth start-up by automatically engaging clutch at low speed during throttle-up and stops brush/pad rotation upon release
- Incrementally adjustable non-marking wheels for safe, smooth operation while allowing operator to control brush/pad pressure
- User-friendly advanced LED instrument panel and ergonomic padded handle
- KWA models feature SafeSense® Emissions Monitoring System; two minute warning light signals automatic shutdown
- Safe-Fill™ cylinder prevents over filling; new and improved quick release strap makes cylinder removal and installation a snap
- Catalytic front mount muffler minimizes harmful emissions
- UL and CGA listed, CARB/EPA certified, CE approved*



BARRACUDA LOW PROFILE PROPANE STRIPPING MACHINE**MODELS:**

BA30KWA/KWC* (76,2 cm)

ENGINE:Kawasaki (431 cc)
OHV v-valve air-cooled**PERFORMANCE:**26,500 sq ft per hour
(± 2400 m²) est.**ENGINE SPEED:**

3600 rpm

BRUSH SIZE:

(2) 16" (40,6 cm) brushes

BRUSH SPEED:

325 rpm

START:

12 v battery

WIDTH:

32" (81,3 cm)

LENGTH:

62" (158 cm)

HEIGHT:

42" (106,7 cm)

WEIGHT:

280 lb (127 kg)

SOUND LEVEL:

89 dB(A)

VIBRATION:Less than 2.5 m/s²**DECK:**Sheet metal construction
with hammertone powder
coat finish**HANDLE:**

Welded steel adjustable

MODELS:

BA34KWA/KWC* (86,4 cm)

ENGINE:Kawasaki (585 cc)
OHV v-valve air-cooled**PERFORMANCE:**30,000 sq ft per hour
(± 2700 m²) est.**ENGINE SPEED:**

3600 rpm

BRUSH SIZE:

(2) 18" (45,7 cm) brushes

BRUSH SPEED:

325 rpm

START:

12 v battery

WIDTH:

36" (91,3 cm)

LENGTH:

63" (160 cm)

HEIGHT:

42" (106,7 cm)

WEIGHT:

335 lb (152 kg)

SOUND LEVEL:

89 dB(A)

VIBRATION:Less than 2.5 m/s²**DECK:**Sheet metal construction
with hammertone powder
coat finish**HANDLE:**

Welded steel adjustable

MODELS:

BA38KWA/KWC* (96,5 cm)

ENGINE:Kawasaki (585 cc)
OHV v-valve air-cooled**PERFORMANCE:**33,500 sq ft per hour
(± 3100 m²) est.**ENGINE SPEED:**

3600 rpm

BRUSH SIZE:

(2) 20" (50,8 cm) brushes

BRUSH SPEED:

325 rpm

START:

12 v battery

WIDTH:

40" (101,6 cm)

LENGTH:

64" (162,6 cm)

HEIGHT:

42" (106,7 cm)

WEIGHT:

355 lb (161 kg)

SOUND LEVEL:

89 dB(A)

VIBRATION:Less than 2.5 m/s²**DECK:**Sheet metal construction
with hammertone powder
coat finish**HANDLE:**

Welded steel adjustable